

Anti-stat

Anti-stat products reduce static build-up by dissipating static charges away from a potentially flammable product. Nearly any polyethylene product can be made using materials containing an anti-static agent that aids in the reduction of static build-up.



Benefits

- Eliminates dry chemical static cling, especially in containers that must remain covered
- Ensures the purity of your product
- Provides protection against drum and pail corrosion
- Ensures the sustainable reuse of your container, keeping drums and pails out of the waste system
- Reduces drum and pail cleaning and reconditioning costs



Anti-stat

Higher Standards

CDF's anti-stat products meet stringent performance ratings. You may select from MIL-SPEC or NFPA standards:

MIL-B-81705C standards require static decay and surface resistivity testing as follows: first the material must be conditioned for 24 hours at 12% +/- 3% relative humidity. The material must meet the 2.0 seconds or less static decay time at 12 +/- 3% relative humidity at a temperature of 73°F +/- 5°F and a surface resistivity of 10¹² or less according to ASTM D257. This requirement represents CDF's highest anti-stat quality.

NFPA-99 (National Fire Protection Association) standards require the material to be conditioned for 24 hours at 50% +/- 2% relative humidity prior to testing and then must meet the static decay time of 0.50 seconds or less at 50% +/- 2% relative humidity at a temperature of 23 +/- 1°C.

CDF also offers Conductive liners. Conductive liners are manufactured from carbon-loaded polyethylene and offer a volume resistivity of less than 300 ohm/cm. Conductive liners meet MIL-P-82646A, MIL-P-82647 and NFPA-56A specifications. Conductive liners are available in 5, 12, 16, 30 and 55 gallon sizes.

Multiple Sizes

Nearly any polyethylene insert, liner, dust cap or cover sheet can be made using materials containing an anti-static agent.

Custom Designs

CDF will always consider custom designs.

Most Popular Products

- 5HD/AS
- 5HD/AS/22
- 3015/AS
- 55AS-11



CDF warrants that its products will be free from defects in material and workmanship for one-hundred eighty (180) days after the date of delivery. Warranty claims must be made in writing no later than five (5) business days after the expiration of the warranty period. CDF's obligations under this warranty are limited solely to replacement of such products as are proven to be defective after CDF's inspection. **Prior to use, the user shall independently determine the suitability of the products for the user's intended use and user assumes all risk and liability whatsoever in connection therewith. CDF products are intended for single use application. Any reuse of the liner and/or fitment voids this warranty.**

CDF EXPRESSLY DISCLAIMS AND EXCLUDES ANY AND ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE RELATING TO THE USE OR PERFORMANCE OF CDF PRODUCTS. CDF SHALL NOT BE LIABLE FOR PERSONAL INJURY OR PROPERTY DAMAGE UNLESS CAUSED SOLELY BY CDF'S NEGLIGENCE. CDF SHALL NOT BE LIABLE FOR LOSS OF PROFIT OR OTHER SPECIAL, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OF CDF PRODUCTS, REGARDLESS OF THE LEGAL THEORY ON WHICH THE CLAIM IS BASED AND EVEN IF CDF HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

For more information or to request a free sample, please call **1-800-443-1920** or visit **www.cdf1.com** today!

CDF Corporation, 77 Industrial Park Road, Plymouth, MA 02360 | ©2014 CDF Corporation | 0414A

