

High-Barrier Foil Liners

The most effective moisture and oxygen barrier for packaging environmentally sensitive products is a liner constructed from an aluminum foil lamination. Moisture barrier liners incorporate an impermeable layer of aluminum foil to ensure the long-term integrity of a wide variety of environmentally sensitive products, including nylon, Surlyn®, EVOH, certain pharmaceuticals and various high value foods.



Benefits

- Manufactured in a clean environment, using cutting-edge CDF1 Smart Seal Technology™ that monitors and ensures consistent, high-quality seals
- Solid track record of protection for 2 years or more, depending on the sensitivity of the product packaged
- Ensures the absolute purity of your product
- Provides an impermeable barrier that allows extended shelf life for even the most hygroscopic materials
- Vertical fill spouts are stronger and easier to use compared to angled fill spouts
- Vertical fill spouts allow packages to be more easily resealed for future use
- Offers a significant improvement in packaging cost per pound compared to smaller containers
- Offers better ergonomics – meaning fewer back injuries – compared to handling smaller, 55 pound bags



High-Barrier Foil Liners

CDF1 Smart Seal Technology™

Using state of the art equipment and quality control standards of the highest caliber, CDF1 Smart Seal Technology ensures the ultimate reliability of IBC foil liners. Proprietary CDF1 Smart Seal Technology optimizes precision and consistency through monitoring the temperature, time and pressure of every seal on every liner.

Multiple Sizes

Foil liners are available in standard Gaylord sizes.

Material Choices

All liners are made in America. The inside layer is made from FDA-approved films.

The laminations available are of foil and metallized polyester.

The film materials used in the manufacture of our IBC liners comply with FDA Regulations 21 CFR 177.1520, CFR 175.105, 177.1390 and CFR 177.1630.

We guarantee that our liners will be constructed from the specified materials and that CDF will not knowingly use materials that are out of specification or could be adulterated. No additives are introduced during the heat-sealing process.

Custom Designs

CDF will always consider custom designs.

Most Popular Products

■ 7-9058



CDF warrants that its products will be free from defects in material and workmanship for one-hundred eighty (180) days after the date of delivery. Warranty claims must be made in writing no later than five (5) business days after the expiration of the warranty period. CDF's obligations under this warranty are limited solely to replacement of such products as are proven to be defective after CDF's inspection. **Prior to use, the user shall independently determine the suitability of the products for the user's intended use and user assumes all risk and liability whatsoever in connection therewith. CDF products are intended for single use application. Any reuse of the liner and/or fitment voids this warranty.**

CDF EXPRESSLY DISCLAIMS AND EXCLUDES ANY AND ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE RELATING TO THE USE OR PERFORMANCE OF CDF PRODUCTS. CDF SHALL NOT BE LIABLE FOR PERSONAL INJURY OR PROPERTY DAMAGE UNLESS CAUSED SOLELY BY CDF'S NEGLIGENCE. CDF SHALL NOT BE LIABLE FOR LOSS OF PROFIT OR OTHER SPECIAL, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OF CDF PRODUCTS, REGARDLESS OF THE LEGAL THEORY ON WHICH THE CLAIM IS BASED AND EVEN IF CDF HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

For more information or to request a free sample, please call **1-800-443-1920** or visit **www.cdf1.com** today!

CDF Corporation, 77 Industrial Park Road, Plymouth, MA 02360 | ©2014 CDF Corporation | 0414A

